

# HARDWOOD



Tasmanian Oak



Black Butt



Spotted Gum



Iron Back



Wolf Grey





Floor:HARDWOOD **TASMANIAN OAK** 20x120cm 8x48'

## HARDWOOD

Hardwood has been designed to decorate living spaces with a contemporary feel and features the natural look of wood. The natural warm colours and shades are inspired from the look of oak, that evokes the earthiness and aged appearance of wood.



Floor:HARDWOOD **SPOTTED GUM** 20x120cm 8x48' 02



Floor: HARDWOOD **IRON BARK HERRINGBONE MOSAIC** MOSAICS



Floor: HARDWOOD **BLACK BUTT** 20x120cm 8x48'

## HARDWOOD

Hardwood has been designed to decorate living spaces with a contemporary feel and features the natural look of wood. The natural warm colours and shades are inspired from the look of oak, that evokes the earthiness and aged appearance of wood.



HARDWOOD  
**Tasmanian Oak**

■ **FORMATS**

20x120

■ **SURFACES**

Matt(Surfacetec)

■ **APPLICATIONS**

- Interior
- Exterior
- Wall
- Floor
- Residential
- Light Commercial

**12**  
**TWELVE**  
RANDOM FACES  
20x120cm



## HARDWOOD

### Black Butt

#### ■ FORMATS

20x120

#### ■ SURFACES

Matt(Surfacetec)

#### ■ APPLICATIONS

Interior  
Exterior  
Wall  
Floor  
Residential  
Light Commercial

# 12

**TWELVE**  
RANDOM FACES  
20x120cm

Black Butt

08

HARDWOOD

Spotted Gum

■ **FORMATS**

20x120

■ **SURFACES**

Matt(Surfacetec)

■ **APPLICATIONS**

Interior  
Exterior  
Wall  
Floor  
Residential  
Light Commercial

**12**

**TWELVE**  
RANDOM FACES  
20x120cm



HARDWOOD

Iron Back

■ **FORMATS**

20x120

■ **SURFACES**

Matt(Surfacetec)

■ **APPLICATIONS**

Interior  
Exterior  
Wall  
Floor  
Residential  
Light Commercial

**12**

**TWELVE**  
RANDOM FACES  
20x120cm

HARDWOOD

Wolf Grey

■ **FORMATS**

20x120

■ **SURFACES**

Matt(Surfacetec)

■ **APPLICATIONS**

Interior  
Exterior  
Wall  
Floor  
Residential  
Light Commercial

**12**

**TWELVE**  
RANDOM FACES  
20x120cm



## TECHNICAL SPECIFICATIONS

TECHNICAL CHARACTERISTIC	STANDARD TEST METHOD	PRESCRIBED VALUES	MANUFACTURER'S VALUES
<b>MEASUREMENT &amp; SURFACE APPEARANCE</b>			
LENGTH	EN ISO 10545-2	±0.6%	±0.1%
WIDTH	EN ISO 10545-2	±0.6%	±0.1%
THICKNESS	EN ISO 10545-2	±5%	±3%
TRANSMUTATION	EN ISO 10545-2	±0.5%	±0.2%
<b>PHYSICAL PROPERTIES</b>			
WATER ABSORPTION	EN ISO 10545-3	≤0.5%	≤0.5%
BREAKING STRENGTH	EN ISO 10545-4	≥1300N	≥1300N
MODULUS OF RUPTURE	EN ISO 10545-4	≥35N/mm <sup>2</sup>	≥35N/mm <sup>2</sup>
RESISTANCE TO ABRASION	EN ISO 10545-7	≤205mm <sup>3</sup>	≤160mm <sup>3</sup>
SLIP RESISTANCE, WET PENDULUM TEST METHOD, SLIDER 96	AS 4586-2013/AMDT1-2017 APPENDIX A	N/A	P4
<b>CHEMICAL PROPERTIES</b>			
RESISTANCE TO CHEMICALS RESISTANCE TO HOUSEHOLD CHEMICALS AND SWIMMING POOL SALTS	EN ISO 10545-13	MINIMUM GB	<b>PASS</b>
RESISTANCE TO STAINING	EN ISO 10545-14 when subjected to chemicals	MINIMUM CLASS 3	<b>PASS</b>

## PACKING SPECIFICATIONS

SERIES	SIZES	PCS / CTN	M <sup>2</sup> / CTN	M <sup>2</sup> / PLT	CTN / PLT	KG / PLT
<b>HARDWOOD</b>	20X120CM	5	1.2	60	50	1400



UNIFORM  
APPEARANCE  
**V1**



SLIGHT  
APPEARANCE  
**V2**



MODERATE  
APPEARANCE  
**V3**



SUBSTANTIAL  
APPEARANCE  
**V4**